



**PR7 VARIABLE BEAM PROFILES (Series III)
COOL BEAM & STANDARD LAMP TYPES
BEAM SPREADS: 15/25deg & 22/40deg**



PR7-M/T & PR7-M/G



PR7-M/G/PL

| LUMINAIRE TYPE | LUMINAIRE DIMENSIONS | | | Lamp | Beam Angles | Approx. Lux at 10M | | |
|----------------|----------------------|--------|-----------|----------|-------------|--------------------|-------|-------|
| | Kg. | Length | X Section | | | 15deg | 25deg | 40deg |
| PR7-W/T | 4.8 | 540 | 157x157 | 650W T27 | 22/40 | N/A | 294 | 196 |
| PR7-M/T | 5.2 | 660 | 157x157 | 650W T27 | 15/25 | 441 | 284 | N/A |
| PR7-W/G | 4.8 | 540 | 157x157 | 800W GKV | 22/40 | N/A | 537 | 358 |
| PR7-M/G | 5.2 | 660 | 157x157 | 800W GKV | 15/25 | 941 | 823 | N/A |
| PR7-W/G/PL | 5.0 | 540 | 198x198 | 800W GKV | 22/40 | N/A | 798 | 493 |
| PR7-M/G/PL | 5.5 | 660 | 198x198 | 800W GKV | 15/25 | 2058 | 980 | N/A |

W/T = Wide Angle Variable Beam Profile with Aluminium Reflector & Base Down Lamp
M/T = Medium Angle Variable Beam Profile with Aluminium Reflector & Base Down Lamp
W/G = Wide Angle Variable Beam Profile with Cool Beam Reflector & Axial Lamp
M/G = Medium Angle Variable Beam Profile with Cool Beam Reflector & Axial Lamp
W/G/PL = Wide Angle Variable Beam Profile with Cool Beam Reflector & Axial Lamp
M/G/PL = Medium Angle Variable Beam Profile with Cool Beam Reflector & Axial Lamp

Luminaire Length includes Rear Grab Handle & Gel Frame Runners

* SEE LAMPS SPEC SHEET FOR LAMP LIFE, COLOUR TEMPS, LAMP BASES ETC.

COOL BEAM Features :

1. Absolutely superior Beam Quality & Focus
2. High output and reduced Power Consumption i.e less load on Dimmers and Air Conditioning
3. Incredible Gel life - temperature at Gel = 30deg C (even less in Metal Halide Units)
4. Long Gobo Life

Standard Features:

1. Power Cut-off Micro Switch
2. Extremely robust and designed for hard usage.
3. Positive Gel Frame/Barndoor Retention System allows these units to stand easily in the nose-down (vertical) position for floor storage.
4. Slider systems are independent of the body structure ensuring trouble-free operation even if the body does sustain some dents or damage.
5. Safety cables are permanently swaged to the rear casting.
6. A Gel Frame is a standard inclusion with each unit.
7. Plug Adaptor (Piggy-back type) is also standard.
8. Beam Shapers (Shutter Blades) are included with all PROFILES
9. All Components are easily accessible via hinged or sliding doors for fast, simple maintenance, with absolutely no pop-rivets being used for fastening purposes.
10. Bodies are constructed using High Pressure Aluminium Die Castings & Aluminium Extrusions
11. The commonly used and readily available "B" Size ROSCO Gobos are accommodated.
11. Custom colouring is available to suit special decor requirements.
12. Weather-proofing for outdoor applications is available.